



XLSERIES

Motorcycle Trailer

Specifications vary by plant



Shown with optional vinyl interior

STANDARD FEATURES

- Tube Main Frame Construction
- 24" O.C. Frame
- 16" O.C. Sidewalls
- 24" O.C. Roof Bows
- Spring Axles
- EZ-Lube Hubs
- 4-Wheel Electric Brakes
- 15" Radial Tires
- 2-5/16" Coupler
- Safety Chains
- 2000# Tongue Jack
- Sand Pad
- 3/4" High Performance Floor
- High Performance Wall Liner
- V-Front
- Aluminum Exterior
- 1 Piece Aluminum Roof
- ATP Fenders
- 24" Stoneguard
- 24" Aluminum Treadplate on Bottom Exterior Sides & Rear
- Ramp Door with Spring Assist & 12" Ramp Door Extension
- 32" Entry Door with Flushlock
- (2) Sidewall Vents
- 7-Way Plug
- LED Tail Lights
- LED Clearance Lights
- (1) Dome Light and Switch
- Beavertail
- (6) Pieces Floor E-Track
- (2) Wheel Chocks
- Automotive Undercoating
- Limited 3 Year Warranty

IN: 877 475 5665 • TX: 866 622 0858 • AZ: 877 541 5665 • UT: 877 544 5665 • PA: 844 661 5665

www.cargoexpress.com

Cargo Express is a family-focused company; building industry-leading products while making safety, innovation and customer service our highest priorities.

	XL MOTORCYCLE TRAILER		
	XLMC7X12TE2	XLMC7X14TE2	XLMC7X16TE2
Overall Length	16'6"	18'6"	20'6"
Width	102"	102"	102"
Height	84"	84"	84"
Interior Length	13'4"	15'4"	17'4"
Interior Width	78 1/2"	78 1/2"	78 1/2"
Interior Height	66"	66"	66"
Platform Height	17"	17"	17"
Rear Opening Ht.	66"	66"	66"
Rear Opening Wd.	76 1/2"	76 1/2"	76 1/2"
Hitch Ball Height	16"	16"	16"
Hitch Ball Size	2 5/16"	2 5/16"	2 5/16"
Brakes	ELECTRIC	ELECTRIC	ELECTRIC
GVWR	7000#	7000#	7000#
Hitch Weight	234#	265#	348#
Curb Weight	2050#	2210#	3160#
Payload Capacity	4950#	4790#	3840#
Tires	15"	15"	15"
Wheels	E-COAT	E-COAT	E-COAT
Frame	TUBE	TUBE	TUBE
Floor	3/4"	3/4"	3/4"
Sidewalls	High Performance Wall Liner	High Performance Wall Liner	High Performance Wall Liner
Tail Lights	LED	LED	LED
Clearance Lights	LED	LED	LED
Dome Light	1	1	1
Switch	STD	STD	STD
Sidewall Vents	2	2	2
Stone Guard	24"	24"	24"
V-Nose	STD	STD	STD
Side Door	32"	32"	32"
Ramp	STD	STD	STD
Sand Pad	STD	STD	STD
Crossmembers	24" OC	24" OC	24" OC
Side Posts	16" OC	16" OC	16" OC
Roof Bows	24" OC	24" OC	24" OC
Axles	SPRING	SPRING	SPRING
EZ Lube	YES	YES	YES
Undercoat	Automotive	Automotive	Automotive

Specifications Subject to Change Without Notice