

	7 x 12	7 x 14	7 x 16	7 x 18	7 x 20	8.5 x 12		
	VE0.410MHED 070	KE8414MHFB-	KE8416MHFB-	KE8418MHFB-	KE8420MHFB-	VE10010MUED 070		
Model #	KE8412MHFB-070	070	070	070	070	KE10212MHFB-070		
CAPACITIES								
GVWR (lbs)			7(000				
GAWR (lbs/axle)		3500						
CHASSIS								
Frame		6" x 2" Steel Tube						
Tongue			6" Extension, 6" x	2" Steel Triple Tub	e e			
Crossmembers			Formed Steel	, 16" On-Center				
Integrated Step(s)						Interior Recessed		
Coupler			2-5/16" /	Adjustable				
Safety Chains			DOT Co	ompliant				
Tongue Jack			7K Drop Le	eg, Set-Back				
Wall Studs		Steel Tube, 16" On-Center						
Roof Bows		Steel Tube, 8" On-Center						
Front Profile		Round						
Stabilizers		Rear Drop-Leg Jacks						
Rear Door			Style Double with	•	•			
Side Door	36" Wide Flush Lock, Additional Barlock and Hasp, Cast Aluminum Holdback							
Vents		Roof Vent Frame, Salem Sidewall Airflow						
Fenders		Smooth Aluminum						
Axle		(2) 3500 lb. Torsion Brake						
Hubs		Easy Lube Rattory Switch, and Lanyard						
Breakaway 		Battery, Switch, and Lanyard ST205/75R15C 6-PR						
Tires								
Wheels				lole Steel				
Exterior Finish				luminum motive				
Undercoating Exterior Fastening				d (Screwless)				
Exterior Trim	2 5" Ton I	Extrusion 3" Rotto		· · · · · · · · · · · · · · · · · · ·	rs, Color Matching	Pear Hoon		
Stone Guard	2.5 1001	Extrusion, 5 Botto		ATP	is, color matching	Keai 1100p		
Roof				nless Aluminum				
Roof Cap			•	PO				
Exterior Storage	(4) Heavy Duty I	Ladder Racks with		(5) Heavy Duty L	adder Racks with	(4) Heavy Duty Ladder Racks with Rear Roller		
Exterior Accessories		ATP and Eng	gineered Wood Ton	igue Cover, Front A	Access Ladder			
Interior Walls			Enginee	red Wood				
Interior Trim			Engineered Woo	d Wall Transitions				
Flooring			3/4" Engin	eered Wood				



Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.



	7 x 12	7 x 14	7 x 16	7 x 18	7 x 20	8.5 x 12		
Interior Lights	(2) 48" 110V Wrap Around LED, (2) LED							
Switches		(1) 110V, (1) Dome Light, 12V, (1) Pair Top Fuel 3-Way, 12V						
Fixtures	(3) Tool Cabinets with Aluminum Work Station	` ,	s with Aluminum Station	(4) Tool Cabinets with Aluminum Work Station		(3) Tool Cabinets with Aluminum Work Station		
Cargo Control		(4) 5000 lb. Recessed D-Rings, Recessed Wall E-Track, One Row						
Connector Plug	Round 7-pin Blade							
Exterior Lights	(1	(2) Rear LED Loading, Full LED, DOT Compliant, Integrated Backup/Taillights						
110v Electrical	(1) Exterior GFI Rece	(1) Exterior GFI Receptacle, 30 Amp, 25 ft. Power Cord, 30 Amp Motor Base Plug, 30 Amp Service Panel, (4) Interior Receptacles						





	8.5 x 14	8.5 x 16	8.5 x 18	8.5 x 20					
Model #	KE10214MHFB-070	KE10216MHFB-070	KE10218MHFB-070	KE10220MHFB-070					
	RETUZITANIII D 070	RETOZIONIII B 070	RETOZIOWIII B 070	RETUZZOWITI D 070					
CAPACITIES									
GVWR (lbs)		70							
GAWR (lbs/axle)	3500								
CHASSIS									
Frame	6" x 2" Steel Tube								
Tongue	6" Extension, 6" x 2" Steel Triple Tube								
Crossmembers		Formed Steel,	16" On-Center						
Integrated Step(s)		Interior F	Recessed						
Coupler		2-5/16" A	djustable						
Safety Chains		DOT Co	mpliant						
Tongue Jack		7K Drop Le							
Wall Studs		Steel Tube, 1							
Roof Bows		Steel Tube, 8							
Front Profile		Rou							
Stabilizers		Rear Drop-	•						
Rear Door		Barn-Style Double with C	• • •						
Side Door	36" Wide Flush Lock, Additional Barlock and Hasp, Cast Aluminum Holdback								
Vents	Roof Vent Frame, Salem Sidewall Airflow								
Fenders	Smooth Aluminum								
Axle	(2) 3500 lb. Torsion Brake								
Hubs	Easy Lube								
Breakaway	Battery, Switch, and Lanyard ST205/75R15C 6-PR								
Tires		15", 5-Hole Steel							
Wheels Exterior Finish	·								
		.030" Aluminum Automotive							
Undercoating Exterior Fastening		VHB Bonded							
Exterior Trim	2 5" Ton Evtrucia	on, 3" Bottom Extrusion, ATP Ra	,	tching Rear Hoon					
Stone Guard	2.5 TOP EXITUSIT	24".		toming iteal 1100p					
Roof		Flat Top Seaml							
Roof Cap		Tiat top ocaliii							
Exterior Storage	(4) Heavy Duty Ladder	Racks with Rear Roller		r Racks with Rear Roller					
Exterior Accessories		ATP and Engineered Wood Tong	, , , , ,						
Interior Walls		Engineer							
Interior Trim		Engineered Wood							
Flooring		3/4" Engine							
Interior Lights		(2) 48" 110V Wrap A	Around LED, (2) LED						
Switches		(1) 110V, (1) Dome Light, 12V	, (1) Pair Top Fuel 3-Way, 12V						
Fixtures	(2) Tool Cabinets with A	Aluminum Work Station	(4) Tool Cabinets with	Aluminum Work Station					



Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.





	8.5 x 14	8.5 x 16	8.5 x 18	8.5 x 20		
Cargo Control	(4)	5000 lb. Recessed D-Rings,	Recessed Wall E-Track, One Ro	W		
Connector Plug	Round 7-pin Blade					
Exterior Lights	(2) Rear LED Loading, Full LED, DOT Compliant, Integrated Backup/Taillights					
110v Electrical	(1) Exterior GFI Receptacle, 30 Amp, 25 ft. Power Cord, 30 Amp Motor Base Plug, 30 Amp Service Panel, (4) Interior Receptacles					





	7 x 12	7 x 14	7 x 16	7 x 18	7 x 20	8.5 x 12			
Madel #	VE0.412MUED 100	KE8414MHFB-	KE8416MHFB-	KE8418MHFB-	KE8420MHFB-	VE10010MUED 100			
Model #	KE8412MHFB-100	100	100	100	100	KE10212MHFB-100			
CAPACITIES									
GVWR (lbs)		9900							
GAWR (lbs/axle)	5000								
CHASSIS									
Frame	6" x 2" Steel Tube								
Tongue			6" Extension, 6" x	2" Steel Triple Tub	e				
Crossmembers				, 16" On-Center					
Integrated Step(s)						Interior Recessed			
Coupler			2-5/16" /	Adjustable					
Safety Chains			DOT C	ompliant					
Tongue Jack		7K Drop Leg, Set-Back							
Wall Studs	Steel Tube, 16" On-Center								
Roof Bows	Steel Tube, 8" On-Center								
Stabilizers	Rear Drop-Leg Jacks								
Rear Door	Barn-Style Double with Cambar and Step Bumper								
Side Door	;	36" Wide Flush Loc	k, Additional Barlo	ck and Hasp, Cast	Aluminum Holdba	ck			
Vents	Roof Vent Frame, Salem Sidewall Airflow								
Fenders		Smooth Aluminum							
Axle			(2) 5200 lb.	Torsion Brake					
Hubs		Easy Lube							
Breakaway		Battery, Switch, and Lanyard							
Tires		ST225/75R15D 8-PR							
Wheels			15", 6-H	lole Steel					
Exterior Finish			.030" A	luminum					
Undercoating			Auto	motive					
Exterior Fastening				d (Screwless)					
Exterior Trim	2.5" Top	Extrusion, 3" Botto			rs, Color Matching	Rear Hoop			
Stone Guard			24'	ATP					
Roof			Flat Top Seam	nless Aluminum					
Roof Cap			Т	PO					
Exterior Storage	(4) Heavy Duty	Ladder Racks with	Rear Roller		adder Racks with Roller	(4) Heavy Duty Ladder Racks with Rear Roller			
Exterior Accessories		ATP and Eng	gineered Wood Tor	igue Cover, Front A	ccess Ladder				
Interior Walls			Enginee	red Wood					
Interior Trim			Engineered Woo	d Wall Transitions					
Flooring			3/4" Engin	eered Wood					
Interior Lights			(2) 48" 110V Wrap	Around LED, (2) LI	D				



Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.

© 2025 Novae LLC



	7 x 12	7 x 14	7 x 16	7 x 18	7 x 20	8.5 x 12		
Switches	(1) 110V, (1) Dome Light, 12V, (1) Pair Top Fuel 3-Way, 12V							
Fixtures	(3) Tool Cabinets with Aluminum Work Station	(2) Tool Cabinets with Aluminum Work Station		(4) Tool Cabinets with Aluminum Work Station		(3) Tool Cabinets with Aluminum Work Station		
Cargo Control		(4) 5000 lb. Recessed D-Rings, Recessed Wall E-Track, One Row						
Connector Plug	Round 7-pin Blade							
Exterior Lights	(2	(2) Rear LED Loading, Full LED, DOT Compliant, Integrated Backup/Taillights						
110v Electrical	(1) Exterior GFI Rece	(1) Exterior GFI Receptacle, 30 Amp, 25 ft. Power Cord, 30 Amp Motor Base Plug, 30 Amp Service Panel, (4) Interior Receptacles						





	8.5 x 14	8.5 x 16	8.5 x 18	8.5 x 20					
Model #	KE10214MHFB-100	KE10216MHFB-100	KE10218MHFB-100	KE10220MHFB-100					
CAPACITIES									
GVWR (lbs)		99	00						
GAWR (lbs/axle)		50	00						
CHASSIS									
Frame	6" x 2" Steel Tube								
Tongue	6" Extension, 6" x 2" Steel Triple Tube								
Crossmembers		Formed Steel,	16" On-Center						
Integrated Step(s)		Interior F	Recessed						
Coupler		2-5/16" A	djustable						
Safety Chains		DOT Co	mpliant						
Tongue Jack		7K Drop Le	g, Set-Back						
Wall Studs		Steel Tube, 1	6" On-Center						
Roof Bows		Steel Tube, 8	3" On-Center						
Stabilizers		Rear Drop-	-						
Rear Door		Barn-Style Double with C	ambar and Step Bumper						
Side Door	36" Wid	e Flush Lock, Additional Barlo	ck and Hasp, Cast Aluminum H	loldback					
/ents	Roof Vent Frame, Salem Sidewall Airflow								
Fenders	Smooth Aluminum								
Axle	(2) 5200 lb. Torsion Brake								
lubs	Easy Lube								
Breakaway	Battery, Switch, and Lanyard								
Tires	ST225/75R15D 8-PR								
Wheels	15", 6-Hole Steel								
Exterior Finish	.030" Aluminum								
Undercoating	Automotive								
Exterior Fastening		VHB Bonded	· · · · · · · · · · · · · · · · · · ·						
Exterior Trim	2.5" Top Extrusion	on, 3" Bottom Extrusion, ATP R	·	tching Rear Hoop					
Stone Guard		24"							
Roof		•	less Aluminum						
Roof Cap			20						
Exterior Storage		Racks with Rear Roller		Racks with Rear Roller					
Exterior Accessories		ATP and Engineered Wood Tong		er					
nterior Walls		_	ed Wood						
nterior Trim		•	l Wall Transitions						
Flooring		3/4" Engine							
nterior Lights		• • • • • • • • • • • • • • • • • • • •	Around LED, (2) LED						
Switches	(2) =	. ,	(1) Pair Top Fuel 3-Way, 12V						
Fixtures	• •	Aluminum Work Station	` '	Aluminum Work Station					
Cargo Control	(4	4) 5000 lb. Recessed D-Rings, I	Recessed Wall E-Track, One Ro	DW					



Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.

© 2025 Novae LLC





	8.5 x 14	8.5 x 16	8.5 x 18	8.5 x 20	
Connector Plug		Round 7-	pin Blade		
Exterior Lights	(2) Rear LED Loading, Full LED, DOT Compliant, Integrated Backup/Taillights				
110v Electrical	(1) Exterior GFI Receptacle	, 30 Amp, 25 ft. Power Cord, 30 Recep) Amp Motor Base Plug, 30 An stacles	np Service Panel, (4) Interior	

