

EX DLX FLAT TOP V-NOSE 3K

	5 x 8	5 x 8	5 x 10	5 x 10	6 x 10	6 x 10		
Model #	KE6008STSV-030	KE6008STSV-035	KE6010STSV-030	KE6010STSV-035	KE7210STSV-030	KE7210STSV-035		
CAPACITIES								
GVWR (lbs)	2990	3500	2990	3500	2990	3500		
GAWR (lbs/axle)	3500							
CHASSIS								
Frame	3" x 2" Steel Tube							
Tongue		3" x 2" Steel Tube						
Crossmembers			Formed Steel,	, 24" On-Center				
Coupler			2" A-	Frame				
Safety Chains			DOT Co	ompliant				
Tongue Jack			2K Couple	er Mounted				
Wall Studs			Steel Tube, 2	24" On-Center				
Roof Bows		Steel Tube, 24" On-Center						
Front Profile			V-N	lose				
Ramp(s)			1500 lb. v	with Assist				
Side Door					32" Wide Flush Lo	ock, Wire Holdback		
Vents			Sidewa	ll Airflow				
Fenders			Smooth .	Aluminum				
Axle	3500 lb. Drop	3500 lb. Drop	3500 lb. Drop	3500 lb. Drop	3500 lb. Drop	3500 lb. Drop		
	Spring Idler	Spring Brake	Spring Idler	Spring Brake	Spring Idler	Spring Brake		
Hubs			Easy	/ Lube				
Breakaway		Battery, Switch,		Battery, Switch,		Battery, Switch,		
		and Lanyard	AT005/3	and Lanyard		and Lanyard		
Tires		ST205/75R15C 6-PR						
Wheels			•	lole Steel				
Exterior Finish				luminum				
Undercoating				motive				
Exterior Fastening		4 Ell D. H E		hing Screws	'a a Dava Hara			
Exterior Trim	1.5" Bottom Extrusion, 1.5" Top Extrusion, Color Matching Rear Hoop 16" ATP							
Stone Guard Roof								
Interior Walls			•	nless Aluminum				
Interior Walls Interior Trim	Engineered Wood							
Ceiling		Vinyl Wall Transitions Lauan Strip						
Flooring				•				
Interior Lights	3/4" Engineered Wood (1) LED							
Switches		(1) Dome Light, 12V						
Connector Plug	Flat 4-pin	Round 7-pin Blade	Flat 4-pin	Round 7-pin Blade	Flat 4-pin	Round 7-pin Blade		
Exterior Lights				OT Compliant		P.II Blade		





EX DLX FLAT TOP V-NOSE 3K

	6 x 10	6 x 12	6 x 12	6 x 14	6 x 14	7 x 12		
Model #	KE7210STSV-050	KE7212STSV-030	KE7212STSV- 035	KE7214STSV- 035	KE7214STSV-030	KE8412STSV-035		
CAPACITIES								
GVWR (lbs)	5000	2990	35	500	2990	3500		
GAWR (lbs/axle)	5200			3500				
CHASSIS								
Frame	4" x 2" Steel Tube	3" x 2" Steel Tube 4" x 2" Steel T						
Tongue	4" x 2" Steel Tube		3" x 2" Steel Tube 4" x 2" Steel T					
Crossmembers			Formed Steel,	24" On-Center				
Coupler			2" A-I	Frame				
Safety Chains			DOT Co	mpliant				
Tongue Jack			2K Couple	r Mounted				
Wall Studs			Steel Tube, 2	4" On-Center				
Roof Bows			Steel Tube, 2	4" On-Center				
Front Profile	V-Nose							
Ramp(s)	1500 lb. with Assist 2500 lb. with Assis							
Side Door	32" Wide Flush Lock, Wire Holdback							
Vents			Sidewal	l Airflow				
Fenders			Smooth A	Aluminum				
Axle	5200 lb. Drop Spring Brake	3500 lb. Drop Spring Idler	3500 lb. Drop	Spring Brake	3500 lb. Drop Spring Idler	3500 lb. Drop Spring Brake		
Hubs			Easy	Lube				
Breakaway	Battery, Switch, and Lanyard		Battery, Switc	h, and Lanyard		Battery, Switch, and Lanyard		
Tires	ST225/75R15D 8-PR			ST205/75R15C	6-PR			
Wheels	15", 6-Hole Steel			15", 5-Hole St	eel			
Exterior Finish			.030" AI	uminum				
Undercoating	Automotive							
Exterior Fastening			Color Match	hing Screws				
Exterior Trim	1.5" Bottom Extrusion, 1.5" Top Extrusion, Color Matching Rear Hoop							
Stone Guard			16"	ATP				
Roof			•	less Aluminum				
Interior Walls	Engineered Wood							
Interior Trim			•	Transitions				
Ceiling	Lauan Strip							
Flooring	3/4" Engineered Wood							
Interior Lights	(1) LED							
Switches	_	<u></u>	, ,	Light, 12V	_			
Connector Plug	Round 7-pin Blade	Flat 4-pin		pin Blade	Flat 4-pin	Round 7-pin Blade		
Exterior Lights			Full LED, DO	T Compliant				







	7 x 12
Model #	KE8412STSV-030
CAPACITIES	
GVWR (lbs)	2990
GAWR (lbs/axle)	3500
CHASSIS	
Frame	3" x 2" Steel Tube, 4" x 2" Steel Tube
Tongue	3" x 2" Steel Tube
Crossmembers	Formed Steel, 24" On-Center
Coupler	2" A-Frame
Safety Chains	DOT Compliant
Tongue Jack	2K Coupler Mounted
Wall Studs	Steel Tube, 24" On-Center
Roof Bows	Steel Tube, 24" On-Center
Front Profile	V-Nose
Ramp(s)	2500 lb. with Assist
Side Door	32" Wide Flush Lock, Wire Holdback
Vents	Sidewall Airflow
Fenders	Smooth Aluminum
Axle	3500 lb. Drop Spring Idler
Hubs	Easy Lube
Tires	ST205/75R15C 6-PR
Wheels	15", 5-Hole Steel
Exterior Finish	.030" Aluminum
Undercoating	Automotive
Exterior Fastening	Color Matching Screws
Exterior Trim	1.5" Bottom Extrusion, 1.5" Top Extrusion, Color Matching Rear Hoop
Stone Guard	16" ATP
Roof	Flat Top Seamless Aluminum
Interior Walls	Engineered Wood
Interior Trim	Vinyl Wall Transitions
Ceiling	Lauan Strip
Flooring Interior Lights	3/4" Engineered Wood (1) LED
Switches	(1) Dome Light, 12V
Connector Plug	Flat 4-pin
Exterior Lights	Full LED, DOT Compliant
Exterior Lights	ruii LED, DOT Compilant





EX DLX FLAT TOP V-NOSE 5K

	6 x 12	6 x 14					
Model #	KE7212STSV-050	KE7214STSV-050					
CAPACITIES							
GVWR (lbs)	50	000					
GAWR (lbs/axle)	52	200					
CHASSIS							
Frame	4" x 2" S	4" x 2" Steel Tube					
Tongue	4" x 2" S	4" x 2" Steel Tube					
Crossmembers	Formed Steel,	24" On-Center					
Coupler	2" A-	Frame					
Safety Chains	DOT Co	ompliant					
Tongue Jack	2K Couple	er Mounted					
Wall Studs	Steel Tube, 2	24" On-Center					
Roof Bows	Steel Tube, 2	24" On-Center					
Front Profile	V-N	lose					
Ramp(s)	1500 lb. v	1500 lb. with Assist					
Side Door	32" Wide Flush Lo	32" Wide Flush Lock, Wire Holdback					
Vents	Sidewal	Sidewall Airflow					
Fenders	Smooth A	Smooth Aluminum					
Axle	5200 lb. Drop	5200 lb. Drop Spring Brake					
Hubs	Easy	Easy Lube					
Breakaway	Battery, Switc	Battery, Switch, and Lanyard					
Tires	ST225/75	ST225/75R15D 8-PR					
Wheels	15", 6-H	15", 6-Hole Steel					
Exterior Finish	.030" A	" Aluminum					
Undercoating	Autor	motive					
Exterior Fastening		hing Screws					
Exterior Trim	•	xtrusion, Color Matching Rear Hoop					
Stone Guard		ATP					
Roof	•	Flat Top Seamless Aluminum					
Interior Walls	•	Engineered Wood					
Interior Trim	•	Vinyl Wall Transitions					
Ceiling		Lauan Strip					
Flooring	-	3/4" Engineered Wood					
Interior Lights	` ,	(1) LED					
Switches	, ,	Dome Light, 12V					
Connector Plug		7-pin Blade					
Exterior Lights	Full LED, DO	OT Compliant					





EX DLX FLAT TOP V-NOSE 7K

	6 x 12	7 x 12	7 x 14	7 x 16	8.5 x 16	8.5 x 18
Model #	KE7212STSV-070	KE8412STSV-070	KE8414STSV-070	KE8416STSV-070	KE10216STSV-070	KE10218STSV-070
CAPACITIES						
GVWR (lbs)	7000					
GAWR (lbs/axle)			35	500		
CHASSIS						
Frame		4" x 2" Ste	eel Tube		6" x 2" S	teel Tube
Tongue		4" x 2" Ste	eel Tube		6" x 2" Steel Triple Tube	
Crossmembers			Formed Steel,	24" On-Center		
Integrated Step(s)					Interior I	Recessed
Coupler			2-5/16"	A-Frame		
Safety Chains			DOT Co	mpliant		
Tongue Jack			2K Couple	er Mounted		
Wall Studs			Steel Tube, 2	24" On-Center		
Roof Bows			Steel Tube, 2	24" On-Center		
Front Profile			V-N	lose		
Ramp(s)	1500 lb. with Assist		2500 lb. with Assist		4000 lb. with Assist	
Side Door		32" Wide Flush Loc	k, Wire Holdback		36" Wide Flush Lo	ck, Wire Holdback
Vents			Sidewal	l Airflow		
Fenders	Smooth Aluminum					
Axle	(2) 3500 lb. Drop Spring Brake					
Hubs			•	Lube		
Breakaway	Battery, Switch, and Lanyard					
Tires	ST205/75R15C 6-PR					
Wheels	15", 5-Hole Steel					
Exterior Finish	.030" Aluminum					
Undercoating	Automotive					
Exterior Fastening	Color Matching Screws					
Exterior Trim	1.5" Bottom Extrusion, 1.5" Top Extrusion, Color Matching Rear Hoop					
Stone Guard	16" ATP					
Roof	Flat Top Seamless Aluminum					
Interior Walls	Engineered Wood					
Interior Trim	Vinyl Wall Transitions					
Ceiling	Lauan Strip					
Flooring	3/4" Engineered Wood					
Interior Lights Switches	(1) LED					
Connector Plug	(1) Dome Light, 12V					
Exterior Lights	Round 7-pin Blade					
Exterior Lights	Full LED, DOT Compliant					





EX DLX FLAT TOP V-NOSE 7K

	8.5 x 20
Model #	KE10220STSV-070
CAPACITIES	
	7000
GVWR (lbs)	7000
GAWR (lbs/axle)	3500
CHASSIS	
Frame	6" x 2" Steel Tube
Tongue	6" x 2" Steel Triple Tube
Crossmembers	Formed Steel, 24" On-Center
Integrated Step(s)	Interior Recessed
Coupler	2-5/16" A-Frame
Safety Chains	DOT Compliant
Tongue Jack	2K Coupler Mounted
Wall Studs	Steel Tube, 24" On-Center
Roof Bows	Steel Tube, 24" On-Center
Front Profile	V-Nose
Ramp(s)	4000 lb. with Assist
Side Door	36" Wide Flush Lock, Wire Holdback
Vents	Sidewall Airflow
Fenders	Smooth Aluminum
Axle	(2) 3500 lb. Drop Spring Brake
Hubs	Easy Lube
Breakaway	Battery, Switch, and Lanyard
Tires	ST205/75R15C 6-PR
Wheels	15", 5-Hole Steel
Exterior Finish	.030" Aluminum
Undercoating	Automotive
Exterior Fastening	Color Matching Screws
Exterior Trim	1.5" Bottom Extrusion, 1.5" Top Extrusion, Color Matching Rear Hoop
Stone Guard	16" ATP
Roof	Flat Top Seamless Aluminum
Interior Walls	Engineered Wood
Interior Trim	Vinyl Wall Transitions
Ceiling	Lauan Strip
Flooring	3/4" Engineered Wood
Interior Lights	(1) LED
Switches	(1) Dome Light, 12V
Connector Plug	Round 7-pin Blade
Exterior Lights	Full LED, DOT Compliant





EX DLX FLAT TOP V-NOSE 10K

	8.5 x 16	8.5 x 18	8.5 x 20	8.5 x 22	8.5 x 24			
Model #	KE10216STSV-100	KE10218STSV-100	KE10220STSV-100	KE10222STSV-100	KE10224STSV-100			
CAPACITIES								
GVWR (lbs)			9900					
GAWR (lbs/axle)	5000							
CHASSIS								
Frame			6" x 2" Steel Tube					
Tongue			6" x 2" Steel Triple Tube					
Crossmembers		F	ormed Steel, 16" On-Cent	er				
Integrated Step(s)			Interior Recessed					
Coupler			2-5/16" A-Frame					
Safety Chains			DOT Compliant					
Tongue Jack			2K Coupler Mounted					
Wall Studs			Steel Tube, 24" On-Cente	r				
Roof Bows			Steel Tube, 24" On-Cente	r				
Front Profile			V-Nose					
Ramp(s)			4000 lb. with Assist					
Side Door		36" V	lide Flush Lock, Wire Holo	dback				
Vents			Sidewall Airflow					
Fenders			Smooth Aluminum					
Axle		(2)) 5200 lb. Drop Spring Bra	ıke				
Hubs			Easy Lube					
Breakaway		В	attery, Switch, and Lanya	rd				
Tires			ST225/75R15D 8-PR					
Wheels			15", 6-Hole Steel					
Exterior Finish			.030" Aluminum					
Undercoating			Automotive					
Exterior Fastening			Color Matching Screws					
Exterior Trim	1.5" Bottom Extrusion, 1.5" Top Extrusion, Color Matching Rear Hoop							
Stone Guard			16" ATP					
Roof		FI	at Top Seamless Aluminu	ım				
Interior Walls			Engineered Wood					
Interior Trim	Vinyl Wall Transitions							
Ceiling			Lauan Strip					
Flooring		3/4" Engineered Wood						
Interior Lights Switches	(1) LED							
Connector Plug	(1) Dome Light, 12V Round 7-pin Blade							
Exterior Lights	Full LED, DOT Compliant							
Exterior Lights			run LED, DOT Compilant					

