



**PRO GT GOOSENECK RACE
PRO GT FLAT TOP FLAT FRONT 14K**

	8.5 x 28	8.5 x 30	8.5 x 32	8.5 x 34
Model #	KE10228PRFBGNRT-140	KE10230PRFBGNRT-140	KE10232PRFBGNRT-140	KE10234PRFBGNRT-140
CAPACITIES				
GVWR (lbs)	14000			
GAWR (lbs/axle)	7000			
CHASSIS				
Frame	8" x 2" Steel Tube			
Tongue	Gooseneck			
Crossmembers	Formed Steel, 16" On-Center			
Coupler	2-5/16" Gooseneck			
Safety Chains	DOT Compliant			
Tongue Jack	Dual 12K, 2-Speed Landing Gear			
Wall Studs	Steel Tube, 16" On-Center			
Roof Bows	Steel Tube, 16" On-Center			
Front Profile	Flat			
Beavertail	48"			
Ramp(s)	16" Extension with Bullnose Cap, (2) Recessed Cam Locks, 4000 lb. with Assist			
Side Door	48" Aluminum Pull-Out Step, 48" Wide Flush Lock, Cast Aluminum Holdback			
Access Doors	16" x 48" in Riser			
Vents	(1) Manual Roof, Sidewall Airflow			
Fenders	Extruded Aluminum			
Axle	(2) 7000 lb. Torsion Brake, Spread Axle Configuration			
Hubs	Easy Lube			
Breakaway	Battery, Switch, and Lanyard			
Tires	ST235/80R16E 10-PR			
Wheels	16", 8-Hole Aluminum			
Exterior Finish	.040" Aluminum			
Undercoating	Automotive			
Exterior Fastening	VHB Bonded (Screwless)			
Exterior Trim	5.5" Bottom Extrusion, ATP Riser Wall, Heavy Duty Truck Body Top Extrusion, Polished Cast Aluminum Roof Corners, Stainless Steel Radius Corners, Stainless Steel Rear Hoop			
Rear Spoiler	6" Stainless Steel Flare with Taper			
Roof	Flat Top Seamless Aluminum			
Roof Cap	Stainless Steel			
Interior Walls	Aluminum Overlay, Engineered Wood			
Interior Trim	Extruded Aluminum Wall Transitions			
Ceiling	Insulation, Vinyl Ceiling Transitions, White Vinyl Liner with Aluminum Coves			
Flooring	3/4" Engineered Wood			
Interior Lights	(2) 11" LED			
Switches	(1) Top Fuel Dome Light, 12V, (1) Top Fuel Load Light, 12V			

Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.





**PRO GT GOOSENECK RACE
PRO GT FLAT TOP FLAT FRONT 14K**

	8.5 x 28	8.5 x 30	8.5 x 32	8.5 x 34
Cargo Control	(4) 5000 lb. Recessed D-Rings			
Connector Plug	Round 7-pin Blade			
Exterior Lights	(2) Rear LED Loading, (4) Additional Stop/Turn/Tail, Full LED, DOT Compliant, Integrated Backup/Taillights			
HVAC	Bracing and Wire for HVAC			



Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.



**PRO GT GOOSENECK RACE
PRO GT FLAT TOP FLAT FRONT 15K**

	8.5 x 30	8.5 x 32	8.5 x 34	8.5 x 36	8.5 x 38
Model #	KE10230PRFBGNRT-150	KE10232PRFBGNRT-150	KE10234PRFBGNRT-150	KE10236PRFBGNRT-150	KE10238PRFBGNRT-150
CAPACITIES					
GVWR (lbs)	15000				
GAWR (lbs/axle)	5000				
CHASSIS					
Frame	8" x 2" Steel Tube				
Tongue	Gooseneck				
Crossmembers	Formed Steel, 16" On-Center				
Coupler	2-5/16" Gooseneck				
Safety Chains	DOT Compliant				
Tongue Jack	Dual 12K, 2-Speed Landing Gear				
Wall Studs	Steel Tube, 16" On-Center				
Roof Bows	Steel Tube, 16" On-Center				
Front Profile	Flat				
Beavertail	48"				
Ramp(s)	16" Extension with Bullnose Cap, (2) Recessed Cam Locks, 4000 lb. with Assist				
Side Door	48" Aluminum Pull-Out Step, 48" Wide Flush Lock, Cast Aluminum Holdback				
Access Doors	16" x 48" in Riser				
Vents	(1) Manual Roof, Sidewall Airflow				
Fenders	Extruded Aluminum				
Axle	(3) 5200 lb. Torsion Brake, Spread Axle Configuration				
Hubs	Easy Lube				
Breakaway	Battery, Switch, and Lanyard				
Tires	ST225/75R15D 8-PR				
Wheels	15", 6-Hole Aluminum				
Exterior Finish	.040" Aluminum				
Undercoating	Automotive				
Exterior Fastening	VHB Bonded (Screwless)				
Exterior Trim	5.5" Bottom Extrusion, ATP Riser Wall, Heavy Duty Truck Body Top Extrusion, Polished Cast Aluminum Roof Corners, Stainless Steel Radius Corners, Stainless Steel Rear Hoop				
Rear Spoiler	6" Stainless Steel Flare with Taper				
Roof	Flat Top Seamless Aluminum				
Roof Cap	Stainless Steel				
Interior Walls	Aluminum Overlay, Engineered Wood				
Interior Trim	Extruded Aluminum Wall Transitions				
Ceiling	Insulation, Vinyl Ceiling Transitions, White Vinyl Liner with Aluminum Coves				
Flooring	3/4" Engineered Wood				
Interior Lights	(2) 11" LED				

Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.





**PRO GT GOOSENECK RACE
PRO GT FLAT TOP FLAT FRONT 15K**

	8.5 x 30	8.5 x 32	8.5 x 34	8.5 x 36	8.5 x 38
Switches	(1) Top Fuel Dome Light, 12V, (1) Top Fuel Load Light, 12V				
Cargo Control	(4) 5000 lb. Recessed D-Rings				
Connector Plug	Round 7-pin Blade				
Exterior Lights	(2) Rear LED Loading, (4) Additional Stop/Turn/Tail, Full LED, DOT Compliant, Integrated Backup/Taillights				
HVAC	Bracing and Wire for HVAC				



Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.



**PRO GT GOOSENECK RACE
PRO GT FLAT TOP FLAT FRONT 16K**

	8.5 x 28	8.5 x 30	8.5 x 32	8.5 x 34
Model #	KE10228PRFBGNRT-160	KE10230PRFBGNRT-160	KE10232PRFBGNRT-160	KE10234PRFBGNRT-160
CAPACITIES				
GVWR (lbs)	16000			
GAWR (lbs/axle)	8000			
CHASSIS				
Frame	8" x 2" Steel Tube			
Tongue	Gooseneck			
Crossmembers	Formed Steel, 16" On-Center			
Coupler	2-5/16" Gooseneck			
Safety Chains	DOT Compliant			
Tongue Jack	Dual 12K, 2-Speed Landing Gear			
Wall Studs	Steel Tube, 16" On-Center			
Roof Bows	Steel Tube, 16" On-Center			
Front Profile	Flat			
Beavertail	48"			
Ramp(s)	16" Extension with Bullnose Cap, (2) Recessed Cam Locks, 4000 lb. with Assist			
Side Door	48" Aluminum Pull-Out Step, 48" Wide Flush Lock, Cast Aluminum Holdback			
Access Doors	16" x 48" in Riser			
Vents	(1) Manual Roof, Sidewall Airflow			
Fenders	Extruded Aluminum			
Axle	(2) 8000 lb. Torsion Brake, Spread Axle Configuration			
Hubs	Oil Bath			
Breakaway	Battery, Switch, and Lanyard			
Tires	215/75R17.5J 18-PR			
Wheels	17.5", 8-Hole Aluminum			
Exterior Finish	.040" Aluminum			
Undercoating	Automotive			
Exterior Fastening	VHB Bonded (Screwless)			
Exterior Trim	5.5" Bottom Extrusion, ATP Riser Wall, Heavy Duty Truck Body Top Extrusion, Polished Cast Aluminum Roof Corners, Stainless Steel Radius Corners, Stainless Steel Rear Hoop			
Rear Spoiler	6" Stainless Steel Flare with Taper			
Roof	Flat Top Seamless Aluminum			
Roof Cap	Stainless Steel			
Interior Walls	Aluminum Overlay, Engineered Wood			
Interior Trim	Extruded Aluminum Wall Transitions			
Ceiling	Insulation, Vinyl Ceiling Transitions, White Vinyl Liner with Aluminum Coves			
Flooring	3/4" Engineered Wood			
Interior Lights	(2) 11" LED			
Switches	(1) Top Fuel Dome Light, 12V, (1) Top Fuel Load Light, 12V			

Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.





**PRO GT GOOSENECK RACE
PRO GT FLAT TOP FLAT FRONT 16K**

	8.5 x 28	8.5 x 30	8.5 x 32	8.5 x 34
Cargo Control	(4) 5000 lb. Recessed D-Rings			
Connector Plug	Round 7-pin Blade			
Exterior Lights	(2) Rear LED Loading, (4) Additional Stop/Turn/Tail, Full LED, DOT Compliant, Integrated Backup/Taillights			
HVAC	Bracing and Wire for HVAC			



Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.



**PRO GT GOOSENECK RACE
PRO GT FLAT TOP FLAT FRONT 21K**

	8.5 x 40	8.5 x 42	8.5 x 44	8.5 x 46	8.5 x 48	8.5 x 50
Model #	KE10240PRFBGNRT-210	KE10242PRFBGNRT-210	KE10244PRFBGNRT-210	KE10246PRFBGNRT-210	KE10248PRFBGNRT-210	KE10250PRFBGNRT-210
CAPACITIES						
GVWR (lbs)	21000					
GAWR (lbs/axle)	7000					
CHASSIS						
Frame	8" x 2" Steel Tube					
Tongue	Gooseneck					
Crossmembers	Formed Steel, 16" On-Center					
Coupler	2-5/16" Gooseneck					
Safety Chains	DOT Compliant					
Tongue Jack	Dual 12K, 2-Speed Landing Gear					
Wall Studs	Steel Tube, 16" On-Center					
Roof Bows	Steel Tube, 16" On-Center					
Front Profile	Flat					
Beavertail	48"					
Ramp(s)	16" Extension with Bullnose Cap, (2) Recessed Cam Locks, 4000 lb. with Assist					
Side Door	48" Aluminum Pull-Out Step, 48" Wide Flush Lock, Cast Aluminum Holdback					
Access Doors	16" x 48" in Riser					
Vents	(1) Manual Roof, Sidewall Airflow					
Fenders	Extruded Aluminum					
Axle	(3) 7000 lb. Torsion Brake, Spread Axle Configuration					
Hubs	Easy Lube					
Breakaway	Battery, Switch, and Lanyard					
Tires	ST235/80R16E 10-PR					
Wheels	16", 8-Hole Aluminum					
Exterior Finish	.040" Aluminum					
Undercoating	Automotive					
Exterior Fastening	VHB Bonded (Screwless)					
Exterior Trim	5.5" Bottom Extrusion, ATP Riser Wall, Heavy Duty Truck Body Top Extrusion, Polished Cast Aluminum Roof Corners, Stainless Steel Radius Corners, Stainless Steel Rear Hoop					
Rear Spoiler	6" Stainless Steel Flare with Taper					
Roof	Flat Top Seamless Aluminum					
Roof Cap	Stainless Steel					
Interior Walls	Aluminum Overlay, Engineered Wood					
Interior Trim	Extruded Aluminum Wall Transitions					
Ceiling	Insulation, Vinyl Ceiling Transitions, White Vinyl Liner with Aluminum Coves					
Flooring	3/4" Engineered Wood					
Interior Lights	(2) 11" LED					
Switches	(1) Top Fuel Dome Light, 12V, (1) Top Fuel Load Light, 12V					
Cargo Control	(4) 5000 lb. Recessed D-Rings					
Connector Plug	Round 7-pin Blade					

Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.





**PRO GT GOOSENECK RACE
PRO GT FLAT TOP FLAT FRONT 21K**

	8.5 x 40	8.5 x 42	8.5 x 44	8.5 x 46	8.5 x 48	8.5 x 50
Exterior Lights	(2) Rear LED Loading, (4) Additional Stop/Turn/Tail, Full LED, DOT Compliant, Integrated Backup/Taillights					
HVAC	Bracing and Wire for HVAC					



Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.



**PRO GT GOOSENECK RACE
PRO GT FLAT TOP FLAT FRONT 21K**

8.5 x 52	
Model #	KE10252PRFBGNRT-210
CAPACITIES	
GVWR (lbs)	21000
GAWR (lbs/axle)	7000
CHASSIS	
Frame	8" x 2" Steel Tube
Tongue	Gooseneck
Crossmembers	Formed Steel, 16" On-Center
Coupler	2-5/16" Gooseneck
Safety Chains	DOT Compliant
Tongue Jack	Dual 12K, 2-Speed Landing Gear
Wall Studs	Steel Tube, 16" On-Center
Roof Bows	Steel Tube, 16" On-Center
Front Profile	Flat
Beavertail	48"
Ramp(s)	16" Extension with Bullnose Cap, (2) Recessed Cam Locks, 4000 lb. with Assist
Side Door	48" Aluminum Pull-Out Step, 48" Wide Flush Lock, Cast Aluminum Holdback
Access Doors	16" x 48" in Riser
Vents	(1) Manual Roof, Sidewall Airflow
Fenders	Extruded Aluminum
Axle	(3) 7000 lb. Torsion Brake, Spread Axle Configuration
Hubs	Easy Lube
Breakaway	Battery, Switch, and Lanyard
Tires	ST235/80R16E 10-PR
Wheels	16", 8-Hole Aluminum
Exterior Finish	.040" Aluminum
Undercoating	Automotive
Exterior Fastening	VHB Bonded (Screwless)
Exterior Trim	5.5" Bottom Extrusion, ATP Riser Wall, Heavy Duty Truck Body Top Extrusion, Polished Cast Aluminum Roof Corners, Stainless Steel Radius Corners, Stainless Steel Rear Hoop
Rear Spoiler	6" Stainless Steel Flare with Taper
Roof	Flat Top Seamless Aluminum
Roof Cap	Stainless Steel
Interior Walls	Aluminum Overlay, Engineered Wood
Interior Trim	Extruded Aluminum Wall Transitions
Ceiling	Insulation, Vinyl Ceiling Transitions, White Vinyl Liner with Aluminum Coves
Flooring	3/4" Engineered Wood
Interior Lights	(2) 11" LED
Switches	(1) Top Fuel Dome Light, 12V, (1) Top Fuel Load Light, 12V
Cargo Control	(4) 5000 lb. Recessed D-Rings
Connector Plug	Round 7-pin Blade
Exterior Lights	(2) Rear LED Loading, (4) Additional Stop/Turn/Tail, Full LED, DOT Compliant, Integrated Backup/Taillights
HVAC	Bracing and Wire for HVAC

Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.





**PRO GT GOOSENECK RACE
PRO GT FLAT TOP FLAT FRONT 24K**

	8.5 x 40	8.5 x 42	8.5 x 44	8.5 x 46	8.5 x 48	8.5 x 50
Model #	KE10240PRFBGNRT- 240	KE10242PRFBGNRT- 240	KE10244PRFBGNRT- 240	KE10246PRFBGNRT- 240	KE10248PRFBGNRT- 240	KE10250PRFBGNRT- 240
CAPACITIES						
GVWR (lbs)	24000					
GAWR (lbs/axle)	8000					
CHASSIS						
Frame	8" x 2" Steel Tube					
Tongue	Gooseneck					
Crossmembers	Formed Steel, 16" On-Center					
Coupler	2-5/16" Gooseneck					
Safety Chains	DOT Compliant					
Tongue Jack	Dual 12K, 2-Speed Landing Gear					
Wall Studs	Steel Tube, 16" On-Center					
Roof Bows	Steel Tube, 16" On-Center					
Front Profile	Flat					
Beavertail	48"					
Ramp(s)	16" Extension with Bullnose Cap, (2) Recessed Cam Locks, 4000 lb. with Assist					
Side Door	48" Aluminum Pull-Out Step, 48" Wide Flush Lock, Cast Aluminum Holdback					
Access Doors	16" x 48" in Riser					
Vents	(1) Manual Roof, Sidewall Airflow					
Fenders	Extruded Aluminum					
Axle	(3) 8000 lb. Torsion Brake, Spread Axle Configuration					
Hubs	Oil Bath					
Breakaway	Battery, Switch, and Lanyard					
Tires	215/75R17.5J 18-PR					
Wheels	17.5", 8-Hole Aluminum					
Exterior Finish	.040" Aluminum					
Undercoating	Automotive					
Exterior Fastening	VHB Bonded (Screwless)					
Exterior Trim	5.5" Bottom Extrusion, ATP Riser Wall, Heavy Duty Truck Body Top Extrusion, Polished Cast Aluminum Roof Corners, Stainless Steel Radius Corners, Stainless Steel Rear Hoop					
Rear Spoiler	6" Stainless Steel Flare with Taper					
Roof	Flat Top Seamless Aluminum					
Roof Cap	Stainless Steel					
Interior Walls	Aluminum Overlay, Engineered Wood					
Interior Trim	Extruded Aluminum Wall Transitions					
Ceiling	Insulation, Vinyl Ceiling Transitions, White Vinyl Liner with Aluminum Coves					
Flooring	3/4" Engineered Wood					
Interior Lights	(2) 11" LED					
Switches	(1) Top Fuel Dome Light, 12V, (1) Top Fuel Load Light, 12V					
Cargo Control	(4) 5000 lb. Recessed D-Rings					
Connector Plug	Round 7-pin Blade					

Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.





**PRO GT GOOSENECK RACE
PRO GT FLAT TOP FLAT FRONT 24K**

	8.5 x 40	8.5 x 42	8.5 x 44	8.5 x 46	8.5 x 48	8.5 x 50
Exterior Lights	(2) Rear LED Loading, (4) Additional Stop/Turn/Tail, Full LED, DOT Compliant, Integrated Backup/Taillights					
HVAC	Bracing and Wire for HVAC					



Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.



**PRO GT GOOSENECK RACE
PRO GT FLAT TOP FLAT FRONT 24K**

8.5 x 52	
Model #	KE10252PRFBGNRT-240
CAPACITIES	
GVWR (lbs)	24000
GAWR (lbs/axle)	8000
CHASSIS	
Frame	8" x 2" Steel Tube
Tongue	Gooseneck
Crossmembers	Formed Steel, 16" On-Center
Coupler	2-5/16" Gooseneck
Safety Chains	DOT Compliant
Tongue Jack	Dual 12K, 2-Speed Landing Gear
Wall Studs	Steel Tube, 16" On-Center
Roof Bows	Steel Tube, 16" On-Center
Front Profile	Flat
Beavertail	48"
Ramp(s)	16" Extension with Bullnose Cap, (2) Recessed Cam Locks, 4000 lb. with Assist
Side Door	48" Aluminum Pull-Out Step, 48" Wide Flush Lock, Cast Aluminum Holdback
Access Doors	16" x 48" in Riser
Vents	(1) Manual Roof, Sidewall Airflow
Fenders	Extruded Aluminum
Axle	(3) 8000 lb. Torsion Brake, Spread Axle Configuration
Hubs	Oil Bath
Breakaway	Battery, Switch, and Lanyard
Tires	215/75R17.5J 18-PR
Wheels	17.5", 8-Hole Aluminum
Exterior Finish	.040" Aluminum
Undercoating	Automotive
Exterior Fastening	VHB Bonded (Screwless)
Exterior Trim	5.5" Bottom Extrusion, ATP Riser Wall, Heavy Duty Truck Body Top Extrusion, Polished Cast Aluminum Roof Corners, Stainless Steel Radius Corners, Stainless Steel Rear Hoop
Rear Spoiler	6" Stainless Steel Flare with Taper
Roof	Flat Top Seamless Aluminum
Roof Cap	Stainless Steel
Interior Walls	Aluminum Overlay, Engineered Wood
Interior Trim	Extruded Aluminum Wall Transitions
Ceiling	Insulation, Vinyl Ceiling Transitions, White Vinyl Liner with Aluminum Coves
Flooring	3/4" Engineered Wood
Interior Lights	(2) 11" LED
Switches	(1) Top Fuel Dome Light, 12V, (1) Top Fuel Load Light, 12V
Cargo Control	(4) 5000 lb. Recessed D-Rings
Connector Plug	Round 7-pin Blade
Exterior Lights	(2) Rear LED Loading, (4) Additional Stop/Turn/Tail, Full LED, DOT Compliant, Integrated Backup/Taillights
HVAC	Bracing and Wire for HVAC

Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.





**PRO GT GOOSENECK RACE
PRO GT FLAT TOP FLAT FRONT 10K**

	8.5 x 28	8.5 x 30	8.5 x 32	8.5 x 34
Model #	KE10228PRFBGNRT-100	KE10230PRFBGNRT-100	KE10232PRFBGNRT-100	KE10234PRFBGNRT-100
CAPACITIES				
GVWR (lbs)	9900			
GAWR (lbs/axle)	5000			
CHASSIS				
Frame	8" x 2" Steel Tube			
Tongue	Gooseneck			
Crossmembers	Formed Steel, 16" On-Center			
Coupler	2-5/16" Gooseneck			
Safety Chains	DOT Compliant			
Tongue Jack	Dual 12K, 2-Speed Landing Gear			
Wall Studs	Steel Tube, 16" On-Center			
Roof Bows	Steel Tube, 16" On-Center			
Front Profile	Flat			
Beavertail	48"			
Ramp(s)	16" Extension with Bullnose Cap, (2) Recessed Cam Locks, 4000 lb. with Assist			
Side Door	48" Aluminum Pull-Out Step, 48" Wide Flush Lock, Cast Aluminum Holdback			
Access Doors	16" x 48" in Riser			
Vents	(1) Manual Roof, Sidewall Airflow			
Fenders	Extruded Aluminum			
Axle	(2) 5200 lb. Torsion Brake, Spread Axle Configuration			
Hubs	Easy Lube			
Breakaway	Battery, Switch, and Lanyard			
Tires	ST225/75R15D 8-PR			
Wheels	15", 6-Hole Aluminum			
Exterior Finish	.040" Aluminum			
Undercoating	Automotive			
Exterior Fastening	VHB Bonded (Screwless)			
Exterior Trim	5.5" Bottom Extrusion, ATP Riser Wall, Heavy Duty Truck Body Top Extrusion, Polished Cast Aluminum Roof Corners, Stainless Steel Radius Corners, Stainless Steel Rear Hoop			
Rear Spoiler	6" Stainless Steel Flare with Taper			
Roof	Flat Top Seamless Aluminum			
Roof Cap	Stainless Steel			
Interior Walls	Aluminum Overlay, Engineered Wood			
Interior Trim	Extruded Aluminum Wall Transitions			
Ceiling	Insulation, Vinyl Ceiling Transitions, White Vinyl Liner with Aluminum Coves			
Flooring	3/4" Engineered Wood			
Interior Lights	(2) 11" LED			
Switches	(1) Top Fuel Dome Light, 12V, (1) Top Fuel Load Light, 12V			

Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.





**PRO GT GOOSENECK RACE
PRO GT FLAT TOP FLAT FRONT 10K**

	8.5 x 28	8.5 x 30	8.5 x 32	8.5 x 34
Cargo Control	(4) 5000 lb. Recessed D-Rings			
Connector Plug	Round 7-pin Blade			
Exterior Lights	(2) Rear LED Loading, (4) Additional Stop/Turn/Tail, Full LED, DOT Compliant, Integrated Backup/Taillights			
HVAC	Bracing and Wire for HVAC			



Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.