



**PRO GT RACE**  
**PRO GT FLAT TOP FLAT FRONT 14K**

	8.5 x 20	8.5 x 22	8.5 x 24	8.5 x 26	8.5 x 28	8.5 x 30
<b>Model #</b>	KE10220PRFBRT-140	KE10222PRFBRT-140	KE10224PRFBRT-140	KE10226PRFBRT-140	KE10228PRFBRT-140	KE10230PRFBRT-140
<b>CAPACITIES</b>						
<b>GVWR (lbs)</b>	14000					
<b>GAWR (lbs/axle)</b>	6000			7000		
<b>CHASSIS</b>						
<b>Frame</b>	8" x 2" Steel Tube					
<b>Tongue</b>	12" Extension, 8" x 2" Steel Triple Tube					
<b>Crossmembers</b>	Formed Steel, 16" On-Center					
<b>Coupler</b>	2-5/16" Adjustable					
<b>Safety Chains</b>	DOT Compliant					
<b>Tongue Jack</b>	7K Drop Leg, Set-Back					
<b>Wall Studs</b>	Steel Tube, 16" On-Center					
<b>Roof Bows</b>	Steel Tube, 16" On-Center					
<b>Front Profile</b>	Flat					
<b>Beavertail</b>	32"					48"
<b>Ramp(s)</b>	16" Extension with Bullnose Cap, (2) Recessed Cam Locks, 4000 lb. with Assist					
<b>Side Door</b>	48" Aluminum Pull-Out Step, 48" Wide Flush Lock, Cast Aluminum Holdback					
<b>Vents</b>	(1) Manual Roof, Sidewall Airflow					
<b>Fenders</b>	Extruded Aluminum					
<b>Axle</b>	(2) 7000 lb. Torsion Brake, Spread Axle Configuration					
<b>Hubs</b>	Easy Lube					
<b>Breakaway</b>	Battery, Switch, and Lanyard					
<b>Tires</b>	ST235/80R16E 10-PR					
<b>Wheels</b>	16", 8-Hole Aluminum					
<b>Exterior Finish</b>	.040" Aluminum					
<b>Undercoating</b>	Automotive					
<b>Exterior Fastening</b>	VHB Bonded (Screwless)					
<b>Exterior Trim</b>	5.5" Bottom Extrusion, Heavy Duty Truck Body Top Extrusion, Polished Cast Aluminum Roof Corners, Stainless Steel Radius Corners, Stainless Steel Rear Hoop					
<b>Stone Guard</b>	24" ATP					
<b>Rear Spoiler</b>	6" Stainless Steel Flare with Taper					
<b>Roof</b>	Flat Top Seamless Aluminum					
<b>Roof Cap</b>	Stainless Steel					
<b>Interior Walls</b>	Aluminum Overlay, Engineered Wood					
<b>Interior Trim</b>	Extruded Aluminum Wall Transitions					
<b>Ceiling</b>	Insulation, Vinyl Ceiling Transitions, White Vinyl Liner with Aluminum Coves					
<b>Flooring</b>	3/4" Engineered Wood					
<b>Interior Lights</b>	(2) 11" LED					

Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.





**PRO GT RACE**  
**PRO GT FLAT TOP FLAT FRONT 14K**

	8.5 x 20	8.5 x 22	8.5 x 24	8.5 x 26	8.5 x 28	8.5 x 30
<b>Switches</b>	(1) Top Fuel Dome Light, 12V, (1) Top Fuel Load Light, 12V					
<b>Cargo Control</b>	(4) 5000 lb. Recessed D-Rings					
<b>Connector Plug</b>	Round 7-pin Blade					
<b>Exterior Lights</b>	(2) Rear LED Loading, (4) Additional Stop/Turn/Tail, Full LED, DOT Compliant, Integrated Backup/Taillights					
<b>HVAC</b>	Bracing and Wire for HVAC					



Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.



**PRO GT RACE**  
**PRO GT FLAT TOP FLAT FRONT 14K**

	8.5 x 32	8.5 x 34
<b>Model #</b>	KE10232PRFBRT-140	KE10234PRFBRT-140
<b>CAPACITIES</b>		
<b>GVWR (lbs)</b>	14000	
<b>GAWR (lbs/axle)</b>	7000	
<b>CHASSIS</b>		
<b>Frame</b>	8" x 2" Steel Tube	
<b>Tongue</b>	12" Extension, 8" x 2" Steel Triple Tube	
<b>Crossmembers</b>	Formed Steel, 16" On-Center	
<b>Coupler</b>	2-5/16" Adjustable	
<b>Safety Chains</b>	DOT Compliant	
<b>Tongue Jack</b>	7K Drop Leg, Set-Back	
<b>Wall Studs</b>	Steel Tube, 16" On-Center	
<b>Roof Bows</b>	Steel Tube, 16" On-Center	
<b>Front Profile</b>	Flat	
<b>Beavertail</b>	48"	
<b>Ramp(s)</b>	16" Extension with Bullnose Cap, (2) Recessed Cam Locks, 4000 lb. with Assist	
<b>Side Door</b>	48" Aluminum Pull-Out Step, 48" Wide Flush Lock, Cast Aluminum Holdback	
<b>Vents</b>	(1) Manual Roof, Sidewall Airflow	
<b>Fenders</b>	Extruded Aluminum	
<b>Axle</b>	(2) 7000 lb. Torsion Brake, Spread Axle Configuration	
<b>Hubs</b>	Easy Lube	
<b>Breakaway</b>	Battery, Switch, and Lanyard	
<b>Tires</b>	ST235/80R16E 10-PR	
<b>Wheels</b>	16", 8-Hole Aluminum	
<b>Exterior Finish</b>	.040" Aluminum	
<b>Undercoating</b>	Automotive	
<b>Exterior Fastening</b>	VHB Bonded (Screwless)	
<b>Exterior Trim</b>	5.5" Bottom Extrusion, Heavy Duty Truck Body Top Extrusion, Polished Cast Aluminum Roof Corners, Stainless Steel Radius Corners, Stainless Steel Rear Hoop	
<b>Stone Guard</b>	24" ATP	
<b>Rear Spoiler</b>	6" Stainless Steel Flare with Taper	
<b>Roof</b>	Flat Top Seamless Aluminum	
<b>Roof Cap</b>	Stainless Steel	
<b>Interior Walls</b>	Aluminum Overlay, Engineered Wood	
<b>Interior Trim</b>	Extruded Aluminum Wall Transitions	
<b>Ceiling</b>	Insulation, Vinyl Ceiling Transitions, White Vinyl Liner with Aluminum Coves	
<b>Flooring</b>	3/4" Engineered Wood	
<b>Interior Lights</b>	(2) 11" LED	
<b>Switches</b>	(1) Top Fuel Dome Light, 12V, (1) Top Fuel Load Light, 12V	
<b>Cargo Control</b>	(4) 5000 lb. Recessed D-Rings	

Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.





**PRO GT RACE  
PRO GT FLAT TOP FLAT FRONT 14K**

**8.5 x 32**

**8.5 x 34**

<b>Connector Plug</b>	Round 7-pin Blade
<b>Exterior Lights</b>	(2) Rear LED Loading, (4) Additional Stop/Turn/Tail, Full LED, DOT Compliant, Integrated Backup/Taillights
<b>HVAC</b>	Bracing and Wire for HVAC



Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.



**PRO GT RACE**  
**PRO GT FLAT TOP FLAT FRONT 16K**

	8.5 x 24	8.5 x 26	8.5 x 28	8.5 x 30	8.5 x 32	8.5 x 34
<b>Model #</b>	KE10224PRFBRT-160	KE10226PRFBRT-160	KE10228PRFBRT-160	KE10230PRFBRT-160	KE10232PRFBRT-160	KE10234PRFBRT-160
<b>CAPACITIES</b>						
<b>GVWR (lbs)</b>	16000					
<b>GAWR (lbs/axle)</b>	8000					
<b>CHASSIS</b>						
<b>Frame</b>	8" x 2" Steel Tube					
<b>Tongue</b>	12" Extension, 8" x 2" Steel Triple Tube					
<b>Crossmembers</b>	Formed Steel, 16" On-Center					
<b>Coupler</b>	2-5/16" Adjustable					
<b>Safety Chains</b>	DOT Compliant					
<b>Tongue Jack</b>	12K Drop Leg, Set-Back					
<b>Wall Studs</b>	Steel Tube, 16" On-Center					
<b>Roof Bows</b>	Steel Tube, 16" On-Center					
<b>Front Profile</b>	Flat					
<b>Beavertail</b>	48"					
<b>Ramp(s)</b>	16" Extension with Bullnose Cap, (2) Recessed Cam Locks, 4000 lb. with Assist					
<b>Side Door</b>	48" Aluminum Pull-Out Step, 48" Wide Flush Lock, Cast Aluminum Holdback					
<b>Vents</b>	(1) Manual Roof, Sidewall Airflow					
<b>Fenders</b>	Extruded Aluminum					
<b>Axle</b>	(2) 8000 lb. Torsion Brake, Spread Axle Configuration					
<b>Hubs</b>	Oil Bath					
<b>Breakaway</b>	Battery, Switch, and Lanyard					
<b>Tires</b>	215/75R17.5J 18-PR					
<b>Wheels</b>	17.5", 8-Hole Aluminum					
<b>Exterior Finish</b>	.040" Aluminum					
<b>Undercoating</b>	Automotive					
<b>Exterior Fastening</b>	VHB Bonded (Screwless)					
<b>Exterior Trim</b>	5.5" Bottom Extrusion, Heavy Duty Truck Body Top Extrusion, Polished Cast Aluminum Roof Corners, Stainless Steel Radius Corners, Stainless Steel Rear Hoop					
<b>Stone Guard</b>	24" ATP					
<b>Rear Spoiler</b>	6" Stainless Steel Flare with Taper					
<b>Roof</b>	Flat Top Seamless Aluminum					
<b>Roof Cap</b>	Stainless Steel					
<b>Interior Walls</b>	Aluminum Overlay, Engineered Wood					
<b>Interior Trim</b>	Extruded Aluminum Wall Transitions					
<b>Ceiling</b>	Insulation, Vinyl Ceiling Transitions, White Vinyl Liner with Aluminum Coves					
<b>Flooring</b>	3/4" Engineered Wood					
<b>Interior Lights</b>	(2) 11" LED					

Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.





**PRO GT RACE  
PRO GT FLAT TOP FLAT FRONT 16K**

	8.5 x 24	8.5 x 26	8.5 x 28	8.5 x 30	8.5 x 32	8.5 x 34
<b>Switches</b>	(1) Top Fuel Dome Light, 12V, (1) Top Fuel Load Light, 12V					
<b>Cargo Control</b>	(4) 5000 lb. Recessed D-Rings					
<b>Connector Plug</b>	Round 7-pin Blade					
<b>Exterior Lights</b>	(2) Rear LED Loading, (4) Additional Stop/Turn/Tail, Full LED, DOT Compliant, Integrated Backup/Taillights					
<b>HVAC</b>	Bracing and Wire for HVAC					



Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.



**PRO GT RACE**  
**PRO GT FLAT TOP FLAT FRONT 21K**

	8.5 x 26	8.5 x 28	8.5 x 30	8.5 x 32	8.5 x 34
<b>Model #</b>	KE10226PRFBRT-210	KE10228PRFBRT-210	KE10230PRFBRT-210	KE10232PRFBRT-210	KE10234PRFBRT-210
<b>CAPACITIES</b>					
<b>GVWR (lbs)</b>	21000				
<b>GAWR (lbs/axle)</b>	7000				
<b>CHASSIS</b>					
<b>Frame</b>	8" x 2" Steel Tube			8" x 2" Steel Tube	
<b>Tongue</b>	12" Extension, 8" x 2" Steel Triple Tube			12" Extension, 8" x 2" Steel Triple Tube	
<b>Crossmembers</b>	Formed Steel, 16" On-Center			Formed Steel, 16" On-Center	
<b>Coupler</b>	2-5/16" Adjustable			2-5/16" Adjustable	
<b>Safety Chains</b>	DOT Compliant			DOT Compliant	
<b>Tongue Jack</b>	12K Drop Leg, Set-Back			12K Drop Leg, Set-Back	
<b>Wall Studs</b>	Steel Tube, 16" On-Center			Steel Tube, 16" On-Center	
<b>Roof Bows</b>	Steel Tube, 16" On-Center			Steel Tube, 16" On-Center	
<b>Front Profile</b>	Flat			Flat	
<b>Beavertail</b>	48"			48"	
<b>Ramp(s)</b>	16" Extension with Bullnose Cap, (2) Recessed Cam Locks, 4000 lb. with Assist			16" Extension with Bullnose Cap, (2) Recessed Cam Locks, 4000 lb. with Assist	
<b>Side Door</b>	48" Aluminum Pull-Out Step, 48" Wide Flush Lock, Cast Aluminum Holdback			48" Aluminum Pull-Out Step, 48" Wide Flush Lock, Cast Aluminum Holdback	
<b>Vents</b>	(1) Manual Roof, Sidewall Airflow				
<b>Fenders</b>	Extruded Aluminum			Extruded Aluminum	
<b>Axle</b>	(3) 7000 lb. Torsion Brake, Spread Axle Configuration			(3) 7000 lb. Torsion Brake, Spread Axle Configuration	
<b>Hubs</b>	Easy Lube			Easy Lube	
<b>Breakaway</b>	Battery, Switch, and Lanyard			Battery, Switch, and Lanyard	
<b>Tires</b>	ST235/80R16E 10-PR			ST235/80R16E 10-PR	
<b>Wheels</b>	16", 8-Hole Aluminum			16", 8-Hole Aluminum	
<b>Exterior Finish</b>	.040" Aluminum			.040" Aluminum	
<b>Undercoating</b>	Automotive			Automotive	
<b>Exterior Fastening</b>	VHB Bonded (Screwless)			VHB Bonded (Screwless)	
<b>Exterior Trim</b>	5.5" Bottom Extrusion, Heavy Duty Truck Body Top Extrusion, Polished Cast Aluminum Roof Corners, Stainless Steel Radius Corners, Stainless Steel Rear Hoop			5.5" Bottom Extrusion, Heavy Duty Truck Body Top Extrusion, Polished Cast Aluminum Roof Corners, Stainless Steel Radius Corners, Stainless Steel Rear Hoop	
<b>Stone Guard</b>	24" ATP			24" ATP	
<b>Rear Spoiler</b>	6" Stainless Steel Flare with Taper			6" Stainless Steel Flare with Taper	
<b>Roof</b>	Flat Top Seamless Aluminum			Flat Top Seamless Aluminum	
<b>Roof Cap</b>	Stainless Steel			Stainless Steel	

Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.





**PRO GT RACE  
PRO GT FLAT TOP FLAT FRONT 21K**

	8.5 x 26	8.5 x 28	8.5 x 30	8.5 x 32	8.5 x 34
<b>Interior Walls</b>	Aluminum Overlay, Engineered Wood			Aluminum Overlay, Engineered Wood	
<b>Interior Trim</b>	Extruded Aluminum Wall Transitions			Extruded Aluminum Wall Transitions	
<b>Ceiling</b>	Insulation, Vinyl Ceiling Transitions, White Vinyl Liner with Aluminum Coves				
<b>Flooring</b>	3/4" Engineered Wood			3/4" Engineered Wood	
<b>Interior Lights</b>	(2) 11" LED			(2) 11" LED	
<b>Switches</b>	(1) Top Fuel Dome Light, 12V, (1) Top Fuel Load Light, 12V			(1) Top Fuel Dome Light, 12V, (1) Top Fuel Load Light, 12V	
<b>Cargo Control</b>	(4) 5000 lb. Recessed D-Rings			(4) 5000 lb. Recessed D-Rings	
<b>Connector Plug</b>	Round 7-pin Blade			Round 7-pin Blade	
<b>Exterior Lights</b>	(2) Rear LED Loading, (4) Additional Stop/Turn/Tail, Full LED, DOT Compliant, Integrated Backup/Taillights			(2) Rear LED Loading, (4) Additional Stop/Turn/Tail, Full LED, DOT Compliant, Integrated Backup/Taillights	
<b>HVAC</b>	Bracing and Wire for HVAC			Bracing and Wire for HVAC	



Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.





**PRO GT RACE**  
**PRO GT FLAT TOP FLAT FRONT 7K**

	8.5 x 20	8.5 x 22	8.5 x 24	8.5 x 26
<b>Model #</b>	KE10220PRFBRT-070	KE10222PRFBRT-070	KE10224PRFBRT-070	KE10226PRFBRT-070
<b>CAPACITIES</b>				
<b>GVWR (lbs)</b>	7000			
<b>GAWR (lbs/axle)</b>	3500			
<b>CHASSIS</b>				
<b>Frame</b>	6" x 2" Steel Tube			
<b>Tongue</b>	12" Extension, 6" x 2" Steel Triple Tube			
<b>Crossmembers</b>	Formed Steel, 16" On-Center			
<b>Coupler</b>	2-5/16" Adjustable			
<b>Safety Chains</b>	DOT Compliant			
<b>Tongue Jack</b>	7K Drop Leg, Set-Back			
<b>Wall Studs</b>	Steel Tube, 16" On-Center			
<b>Roof Bows</b>	Steel Tube, 16" On-Center			
<b>Front Profile</b>	Flat			
<b>Beavertail</b>	32"	48"		
<b>Ramp(s)</b>	16" Extension with Bullnose Cap (Both Ramps), (2) Recessed Cam Locks, 4000 lb. with Assist			
<b>Side Door</b>	48" Aluminum Pull-Out Step, 48" Wide Flush Lock, Cast Aluminum Holdback			
<b>Vents</b>	(1) Manual Roof, Sidewall Airflow			
<b>Fenders</b>	Extruded Aluminum			
<b>Axle</b>	(2) 3500 lb. Torsion Brake, Spread Axle Configuration			
<b>Hubs</b>	Easy Lube			
<b>Breakaway</b>	Battery, Switch, and Lanyard			
<b>Tires</b>	ST205/75R15C 6-PR			
<b>Wheels</b>	15", 5-Hole Aluminum			
<b>Exterior Finish</b>	.030" Aluminum			
<b>Undercoating</b>	Automotive			
<b>Exterior Fastening</b>	VHB Bonded (Screwless)			
<b>Exterior Trim</b>	5.5" Bottom Extrusion, Heavy Duty Truck Body Top Extrusion, Polished Cast Aluminum Roof Corners, Stainless Steel Radius Corners, Stainless Steel Rear Hoop			
<b>Stone Guard</b>	24" ATP			
<b>Rear Spoiler</b>	6" Stainless Steel Flare with Taper			
<b>Roof</b>	Flat Top Seamless Aluminum			
<b>Roof Cap</b>	Stainless Steel			
<b>Interior Walls</b>	Aluminum Overlay, Engineered Wood			
<b>Interior Trim</b>	Extruded Aluminum Wall Transitions			
<b>Ceiling</b>	Insulation, Vinyl Ceiling Transitions, White Vinyl Liner with Aluminum Coves			
<b>Flooring</b>	3/4" Engineered Wood			
<b>Interior Lights</b>	(2) 11" LED			
<b>Switches</b>	(1) Top Fuel Dome Light, 12V, (1) Top Fuel Load Light, 12V			

Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.





**PRO GT RACE**  
**PRO GT FLAT TOP FLAT FRONT 7K**

	8.5 x 20	8.5 x 22	8.5 x 24	8.5 x 26
<b>Cargo Control</b>	(4) 5000 lb. Recessed D-Rings			
<b>Connector Plug</b>	Round 7-pin Blade			
<b>Exterior Lights</b>	(2) Rear LED Loading, (4) Additional Stop/Turn/Tail, Full LED, DOT Compliant, Integrated Backup/Taillights			
<b>HVAC</b>	Bracing and Wire for HVAC			



Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.



**PRO GT RACE**  
**PRO GT FLAT TOP FLAT FRONT 10K**

	8.5 x 20	8.5 x 22	8.5 x 24	8.5 x 26	8.5 x 28	8.5 x 30
<b>Model #</b>	KE10220PRFBRT-100	KE10222PRFBRT-100	KE10224PRFBRT-100	KE10226PRFBRT-100	KE10228PRFBRT-100	KE10230PRFBRT-100
<b>CAPACITIES</b>						
<b>GVWR (lbs)</b>	9900					
<b>GAWR (lbs/axle)</b>	5000					
<b>CHASSIS</b>						
<b>Frame</b>	6" x 2" Steel Tube				8" x 2" Steel Tube	
<b>Tongue</b>	12" Extension, 6" x 2" Steel Triple Tube				12" Extension, 8" x 2" Steel Triple Tube	
<b>Crossmembers</b>	Formed Steel, 16" On-Center					
<b>Coupler</b>	2-5/16" Adjustable					
<b>Safety Chains</b>	DOT Compliant					
<b>Tongue Jack</b>	7K Drop Leg, Set-Back					
<b>Wall Studs</b>	Steel Tube, 16" On-Center					
<b>Roof Bows</b>	Steel Tube, 16" On-Center					
<b>Front Profile</b>	Flat					
<b>Beavertail</b>	32"	48"				
<b>Ramp(s)</b>	16" Extension with Bullnose Cap, (2) Recessed Cam Locks, 4000 lb. with Assist					
<b>Side Door</b>	48" Aluminum Pull-Out Step, 48" Wide Flush Lock, Cast Aluminum Holdback					
<b>Vents</b>	(1) Manual Roof, Sidewall Airflow					
<b>Fenders</b>	Extruded Aluminum					
<b>Axle</b>	(2) 5200 lb. Torsion Brake, Spread Axle Configuration					
<b>Hubs</b>	Easy Lube					
<b>Breakaway</b>	Battery, Switch, and Lanyard					
<b>Tires</b>	ST225/75R15D 8-PR					
<b>Wheels</b>	15", 6-Hole Aluminum					
<b>Exterior Finish</b>	.040" Aluminum					
<b>Undercoating</b>	Automotive					
<b>Exterior Fastening</b>	VHB Bonded (Screwless)					
<b>Exterior Trim</b>	5.5" Bottom Extrusion, Heavy Duty Truck Body Top Extrusion, Polished Cast Aluminum Roof Corners, Stainless Steel Radius Corners, Stainless Steel Rear Hoop					
<b>Stone Guard</b>	24" ATP					
<b>Rear Spoiler</b>	6" Stainless Steel Flare with Taper					
<b>Roof</b>	Flat Top Seamless Aluminum					
<b>Roof Cap</b>	Stainless Steel					
<b>Interior Walls</b>	Aluminum Overlay, Engineered Wood					
<b>Interior Trim</b>	Extruded Aluminum Wall Transitions					
<b>Ceiling</b>	Insulation, Vinyl Ceiling Transitions, White Vinyl Liner with Aluminum Coves					
<b>Flooring</b>	3/4" Engineered Wood					
<b>Interior Lights</b>	(2) 11" LED					

Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.





**PRO GT RACE**  
**PRO GT FLAT TOP FLAT FRONT 10K**

	8.5 x 20	8.5 x 22	8.5 x 24	8.5 x 26	8.5 x 28	8.5 x 30
<b>Switches</b>	(1) Top Fuel Dome Light, 12V, (1) Top Fuel Load Light, 12V					
<b>Cargo Control</b>	(4) 5000 lb. Recessed D-Rings					
<b>Connector Plug</b>	Round 7-pin Blade					
<b>Exterior Lights</b>	(2) Rear LED Loading, (4) Additional Stop/Turn/Tail, Full LED, DOT Compliant, Integrated Backup/Taillights					
<b>HVAC</b>	Bracing and Wire for HVAC					



Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.



**PRO GT RACE**  
**PRO GT FLAT TOP FLAT FRONT 10K**

**8.5 x 32**

<b>Model #</b>	KE10232PRFBRT-100
<b>CAPACITIES</b>	
<b>GVWR (lbs)</b>	9900
<b>GAWR (lbs/axle)</b>	5000
<b>CHASSIS</b>	
<b>Frame</b>	8" x 2" Steel Tube
<b>Tongue</b>	12" Extension, 8" x 2" Steel Triple Tube
<b>Crossmembers</b>	Formed Steel, 16" On-Center
<b>Coupler</b>	2-5/16" Adjustable
<b>Safety Chains</b>	DOT Compliant
<b>Tongue Jack</b>	7K Drop Leg, Set-Back
<b>Wall Studs</b>	Steel Tube, 16" On-Center
<b>Roof Bows</b>	Steel Tube, 16" On-Center
<b>Front Profile</b>	Flat
<b>Beavertail</b>	48"
<b>Ramp(s)</b>	16" Extension with Bullnose Cap, (2) Recessed Cam Locks, 4000 lb. with Assist
<b>Side Door</b>	48" Aluminum Pull-Out Step, 48" Wide Flush Lock, Cast Aluminum Holdback
<b>Vents</b>	(1) Manual Roof, Sidewall Airflow
<b>Fenders</b>	Extruded Aluminum
<b>Axle</b>	(2) 5200 lb. Torsion Brake, Spread Axle Configuration
<b>Hubs</b>	Easy Lube
<b>Breakaway</b>	Battery, Switch, and Lanyard
<b>Tires</b>	ST225/75R15D 8-PR
<b>Wheels</b>	15", 6-Hole Aluminum
<b>Exterior Finish</b>	.040" Aluminum
<b>Undercoating</b>	Automotive
<b>Exterior Fastening</b>	VHB Bonded (Screwless)
<b>Exterior Trim</b>	5.5" Bottom Extrusion, Heavy Duty Truck Body Top Extrusion, Polished Cast Aluminum Roof Corners, Stainless Steel Radius Corners, Stainless Steel Rear Hoop
<b>Stone Guard</b>	24" ATP
<b>Rear Spoiler</b>	6" Stainless Steel Flare with Taper
<b>Roof</b>	Flat Top Seamless Aluminum
<b>Roof Cap</b>	Stainless Steel
<b>Interior Walls</b>	Aluminum Overlay, Engineered Wood
<b>Interior Trim</b>	Extruded Aluminum Wall Transitions
<b>Ceiling</b>	Insulation, Vinyl Ceiling Transitions, White Vinyl Liner with Aluminum Coves
<b>Flooring</b>	3/4" Engineered Wood
<b>Interior Lights</b>	(2) 11" LED
<b>Switches</b>	(1) Top Fuel Dome Light, 12V, (1) Top Fuel Load Light, 12V
<b>Cargo Control</b>	(4) 5000 lb. Recessed D-Rings

Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.





**PRO GT RACE  
PRO GT FLAT TOP FLAT FRONT 10K**

**8.5 x 32**

<b>Connector Plug</b>	Round 7-pin Blade
<b>Exterior Lights</b>	(2) Rear LED Loading, (4) Additional Stop/Turn/Tail, Full LED, DOT Compliant, Integrated Backup/Taillights
<b>HVAC</b>	Bracing and Wire for HVAC



Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.